

NUMEDIC

superior dairy technology

HYDRANTS

A range of high quality hydrants for 90mm OD Effluent Pipe. Manufactured from hot dipped galvanised steel and supplied with high quality Bauer fittings they are built to last. Double brackets are standard.



EFFLUENT PIPE

Suppliers of high density pipes for all rural applications. Effluent Pipe is available in a range of sizes for mainline and draghose to a travelling irrigator. Pipe for water reticulation is also available in a wide range of sizes.



PONTOONS



CAMLOCKS

Full range of camlocks. These are heavy duty agricultural grade fittings that have a smooth, reliable cam lever operation. High accuracy on machining tolerances ensure an accurate fit on installation.



AGITATORS/STIRRERS

A range of multi-directional electrically powered short and long shafted models with shaft lengths to 2.4 metres. The shafts are manufactured from high tensile steel and are extremely robust. There are no submerged bearings which allows for years of trouble free operation. They provide a simple yet effective stirring action and are ideal for vigorously stirring solids to keep them in suspension.



STATIONARY IRRIGATORS

Suitable for use on hilly farms and steeper sidings. Rotation angles of 0 to 360 degrees can be chosen.

An adjustable and intermittent jet-breaker allows for a uniform distribution of liquid over the irrigated area.

Supplied with a range of nozzles for different application rates.



Numedic pontoons have been designed for use in both tanks and large ponds. The pond pontoon is fitted with 6.5 metre long arm that carries the effluent as well as the power cables and can be pivoted to the side of the pond for easy and safe access. Longer arms can be fabricated to suit if required.

Pontoons for concrete tanks are supplied with guide rails to hold the pontoon in the centre of the tank and allow the pontoon and pump to float up and down.

Electrically powered stirrers can be easily fitted to all of our pontoon designs.